
Product	VALUE fold down grab bar with leg, fixed height
Item number	R1101000
	VVS:615722400 NRF:6191641 EAN:5708590176413 HMI: 25412 NBS:N13:436 DB: 2076621 FDA: ILS/D135866
Color	White
Product description	Fold down grab bar with leg, fixed, foldable, length 33.5", height 33.5''. The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately. VALUE fold down grab bar with leg, fixed, foldable, length 33.5", height 33.5''. The ergonomic design gives a secure and comfortable grip as well as a good sense of where the support arm ends. Materials: Rilsan-coated steel, pressure-cast aluminium, plastic. Incl. fixing bolts for brick wall. Plugs depend on wall type and must be ordered separately.
Adjustability	Fixed mounting
Product capacity	Maximum load: 300 lbs. When the fold down grab bar is loaded with 300 lbs, each mounting bolt is loaded with 180 lbs.
Materials	asic material: Steel Surface material: Rilsan End cap: Nylon (PA)




Product	VALUE fold down grab bar with leg, fixed height
Item number	R1101000
Ergonomy	Provides firm support when you are sitting, standing, or transferring to and from a toilet. Good, broad support surface for the hand and arm. The rounded form gives a firm and comfortable grip.
Features	The grab bar can fold up when not in use or to make more space. With leg for extra support.
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged. For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.
Declaration of conformity	This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices.

PRESSALIT®


Product	VALUE fold down grab bar with leg, fixed height
Item number	R1101000


Mounting in different wall types



Concrete >B25


V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included.
Plugs to be ordered separately.






Solid Brick >= Mz12


V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included.
Plugs to be ordered separately.






Solid Sand Lime Brick >= Hlz12


V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included.
Plugs to be ordered separately.






Aerated Concrete P4


V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included.
Plugs to be ordered separately.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood

V8593 - 4 countersunk bolts Ø10 x 80, with white screw covers are included.
Plugs to be ordered separately.





Product	VALUE fold down grab bar with leg, fixed height
Item number	R1101000



Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood


Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.






Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch)

Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.





Drywall (2 x 12,5 mm) water-resistant

Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.



Bolts for wall fixing are included. It is the responsibility of the installer to ensure that suitable plugs are used. Please see mounting instruction.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com