




# PRESSALIT®

<b>Product</b> <b>Item number</b>	VALUE mounting plate, manually height adjustable R1214000
<b>Color</b>	VVS:654011410 NRF:6191676 EAN:5708590176499 HMI: 25578 NBS:N13:30,335 White
<b>Product description</b>	<div>  </div> <p>Mounting plate incl. brackets for wallmounted sink, height adjustable 5.9" (recommendation R2085/R2087 flexible feed/waste system). Incl. wall mounting kit</p> <p>Mounting plate incl. brackets for wallmounted sink, height adjustable 5.9". (recommendation R2085/R2087 flexible feed/waste system). Incl. wall mounting kit</p>
<b>Adjustability</b> <b>Adjustment height</b> <b>Product capacity</b>	Height adjustable 5,91 inch <p>Maximum load: 176 lbs.          Suitable for sinks weighing no more than 49 lbs.          When the sink is loaded with 176 lbs, each wall fastener will be carrying 49 lbs.  <i>Sink brackets need to be able to carry the weight of the sink, as well as support the weight of the person who is leaning against the sink or who is using the sink to rise from seated position.</i>  <b>Neither sink nor sink bracket are intended to carry the full body weight of a person, and the test methods applicable to sink brackets reflect this: ISO 17966 prescribes a static test on the front edge of the sink at 75% of maximum user weight, i.e. when the maximum load on a sink bracket is given as 176 lbs and the wash basin weighs 49 lbs, it is – according to ISO 17966 – the equivalent of a user weighing 170 lbs leaning on the front edge of the wash basin.</b></p>
<b>Materials</b>	Core material: Steel Surface material: Rilsan
<b>Features</b>	Height adjustable 5.9".
<b>Warranty</b>	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.



# PRESSALIT®

<b>Product</b>	VALUE mounting plate, manually height adjustable
<b>Item number</b>	R1214000
<b>Cleaning</b>	<p>This product should be cleaned with hot water or a mild cleaning solution. Do not use corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>For surface disinfection, chlorine-based disinfectants may be used according to the product specification and safety precautions for these products.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p><b>DISINFECTANTS:</b> CaviCide</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p>
<b>Declaration of conformity</b>	<p>This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices.</p>

[pressalit.com](http://pressalit.com)

# PRESSALIT®