
PRESSALIT®

Product	Lift for countertop, electrically height adjustable
Item number	RK1712
	EAN:5708590265940



Product description	The name INDIVO relates to the individual configuration of the products. Lift for countertop, with 2 motors and switches. Including 3 brackets and transformer. Lengths from 55.2 - 78.7". Height adjustable up to 11.8". Incl. mounting kit for brick wall. Please state desired length when ordering.
Adjustability	Height adjustable
Adjustment height	11,82 inch
Product capacity	Maximum load (evenly distributed): 220 lbs including countertop.
Speed up	Speed up: 0,79 inch/s Speed down: 0,79 inch/s
Noise level	45 dB
Materials	Material: Telescopic leg: Aluminium, ABS plastic Cross braces: Aluminium Brackets: Steel Cable tray: ABS plastic Switches: ABS plastic Surface treatment: Brackets: Powder lacquered (grey RAL 9006)

Product	Lift for countertop, electrically height adjustable
Item number	RK1712
Ergonomy	An electric height-adjustable kitchen countertop is ideal in all situations where various users - both seated and standing - use the same kitchen. This is equally true in private homes as well as larger centers with common kitchen facilities such as group homes and care centers.
Features	Lift heights are adjusted via switches in the front edge. Operating switches can be placed wherever you want in the front edge. The switches are color-coded - aluminium to operate countertops and red to operate wall cabinets. Lifts can be adapted to most standard kitchen components. Lifts are available for countertops of any length between 23.6" and 118.1".
Actuator (motor)	DB4 Deskline (Linak) 1000 N, IP22
Control box	CBD6 (Linak), IP22
Wired remote control	HB53 (Linak), IPX1
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date.
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate. DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.

Product	Lift for countertop, electrically height adjustable
Item number	RK1712

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com