



PRESSALIT®

| | |
|----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Item number | PLUS sink bracket with cordless remote control, electrically height adjustable R4752-93 |
| Product description | <div data-bbox="1059 495 1358 831" data-label="Image"> </div> <p>PLUS sink brackets are available in electrically, pneumatically and manually height adjustable versions. They are suitable for wall-mounting or for fitting to Pressalit PLUS wall tracks.</p> <p>PLUS sink bracket, powered with cordless remote control, electrically height adjustable by 11.8". Recommendation: Flexible feed and waste system R2085/R2087. Materials: Aluminium and ABS polymer. Incl. mounting bolts for sink, incl. mounting material for brick wall. Will be discontinued no later than 12/31-2019. Subject to availability.</p> |
| Adjustability Adjustment height Product capacity Speed up Noise level | Height adjustable 11,82 inch <p>This product has been tested statically up to 440 lbs. As the European standard for technical aids for disabled, EN 12182:2012, requires a static test with safety factor 1.5, the nominal maximum load for this product is therefore 300 lbs. During height adjustment, maximum load is 220 lbs.</p> Speed up: 0,79 inch/s Speed down: 0,91 inch/s 45 dB |
| Materials Ergonomy | <p>The sink bracket is primarily made of 3/8" anodized aluminium. The ends of the bracket cover are capped with ABS polymer. The bracket is available with a lever control consisting of an ABS polymer switch at the end of an anodized aluminium arm</p> <p>The height of the sink is easily adjusted the lever control. The sink bracket is compatible with all types of bolt-mounted sink. It's rounded, sleek design makes it easy to clean thoroughly.</p> |



| | |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product | PLUS sink bracket with cordless remote control, electrically height adjustable |
| Item number | R4752-93 |
| Features | The user can easily make height adjustments independently using the electrically operated sink bracket. |
| Mains connection (V) | 120 |
| Actuator (motor) | LA27CS (Linak) 1500N, IPX6 |
| Control box | TR6 (Linak) IPX0 |
| Power consumption (maximum load) | Power consumption by maximum load: 75 W Power consumption by standby: 1,5 W |
| Warranty | Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date. |
| Cleaning | <p>This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.</p> <p>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.</p> <p>DISINFECTANTS: CaviCide</p> <p>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.</p> <p>DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water.</p> |



PRESSALIT®

| | |
|--------------------|--------------------------------------------------------------------------------|
| Product | PLUS sink bracket with cordless remote control, electrically height adjustable |
| Item number | R4752-93 |

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com

PRESSALIT®