

PRESSALIT.

Product Item number	SCT 1000 shower change table, electrically height adjustable R8402000-93		
	EAN:5708590317977 FDA: INQ/D124319		
Color	White		
Product description	Pressalit offers a variety of mobile and wall-hung, height-adjustable and fixed heigh shower and changing tables of high quality. They are designed to provide a stable platform for showering and changing adults and children with reduced mobility. These tables can be used in schools, institutions, hospitals and private homes an are all designed to be durable, comfortable and easy to clean. The design and flexibility of the tables ensures optimal working conditions for the carer as well as a high level of comfort and safety for the user.		
	SCT 1000 shower change table, powered, height adjustable 15.8"; from 18.9" - 34 with wired hand control Foldable. Incl. safety rail. Outer measurements 30.1" x 55.1. Materials: Rilsan coated steel and PVC-coated canvas (phthalate free). Excl. mounting kit.		
Adjustability	Height adjustable		
Adjustment height	15,76 inch		
Product capacity	aximum load: 331 lbs. Then the table is loaded with 331 lbs, each mounting bolt supports 44 lbs. This product has been tested statically with a load of 830 lbs as the IEC 60601- andard requires testing with a safety factor.		
Speed up	Speed up: 0,59 inch/s Speed down: 0,79 inch/s		
Noise level	48 dB		
Materials	The table is made from practical and durable PVC canvas which is phthalate free. The frame is powder-coated steel. Material: Steel, PVC.		



PRESSALIT.

Product	SCT 1000 shower change table, electrically height adjustable		
Item number	R8402000-93		
Ergonomy	Caregivers can easily set the height of the table, enabling them to obtain the correct working position. This ensures safe showering and changing for the user as well as minimizing the risk of back injury for the caregiver.		
Features	Electric with wired hand control – the red buttons clearly indicate "Up" and "Down" The wired hand control comes with a holder for fitting to the wall. The integrated pneumatic cylinders enable the table to be folded out of the way whot in use to maximize floor space in front of the unit. Splash curtain (optional) for the changing table protects the caregiver against splashing.		
Mains connection (V)	120		
Actuator (motor)	LA31 Careline, (Linak), 4000 N, IPX6		
Control box	CB9 Careline, (Linak), IPX6		
Wired remote control	HB3 (Linak), IP66		
Power consumption (maximum load)	Power consumption by maximum load: 70 W Power consumption by standby: 2 W		
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. NOTICE If the product is placed in an atmosphere heavy in salt or chloride, the warranty will be reduced from the normal 3 years to 1 year. Salt and chloride have a corrosive effect on the products components and will cause a decrease in the life expectancy of the product.		
Cleaning	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS: CaviCide Accel PREVention Wipes Lingettes		
	The product must be wiped down with a soft rag wrung out in clear water immediate after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		



PRESSALIT®

Product				
Item number				

SCT 1000 shower change table, electrically height adjustable

R8402000-93

Mounting in different wall types

Woulding in different wall types				
	Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Brick >= Mz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Solid Sand Lime Brick >= Hlz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.			
	Aerated Concrete P4 V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14. To be ordered separately.			
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.			



PRESSALIT®

Product Item number	SCT 1000 shower change table, electrically height at R8402000-93	djustable
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant	
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

pressalit.com