

PRESSALIT.

Product	Changing table, 31.5" x 70.9", electrically height adjustable, with sanitary appliances
Item number	R8685000
item number	
	VV3.777030330
	NRF:7501984
	EAN:5708590338446
	HMI: 100177
Color	White 46.02
Product description	Pressalit offers a wide variety of changing tables designed for use in daycare facilities. The tables are available in several sizes and models, either free standing wall-hung. The fold away feature in wall-hung tables is useful where space is limited. The wall-hang tables with low start are essential for daycare or preschool facilities. Even toddlers can climb onto the table themselves, without the staff lifting them.
	Changing table, wall-mounted, low start, with sink/faucet, 31.5" x 70.9". With motor and transformer, height adjustable from 11.8" - 39.4", with hand control and safety stop function. Laminate worktop with inset stainless steel sink, incl. lever operated faucet, feed/waste system and 2 wire baskets. Materials: Laminate and powder-lacquered steel. Excl. fixing kit.
Adjustability	Height adjustable
Adjustment height	27,58 inch
Product capacity	Max load: 165 lbs.
Speed up	Speed up: 1,5 inch/s Speed down: 1,5 inch/s
Noise level	48 dB
Materials	Lifting unit and baskets: Powder-coated steel. Countertop: Melamine. Waste pipe: Polyurethane, PVC and steel. The flexible waste pipe is very resistant both chemical and physical influences. It is flame retardant and withstands temperatures from -30°C to +110°C.



PRESSALIT.

ergonomically correct height. The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves. Thereby unnecessary lifting is avoided. Easy-to-clean surfaces ensure optimum hygiene. Undermount sink and tap. Integrated safety system prevents entrapment. 230 Actuator (motor) Control box CBD6 (Linak), IP20 Wired remote control Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Warranty Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide		
Ergonomy The smooth height adjustment ensures that it is always possible to set the table at an ergonomically correct height. The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves. Thereby unnecessary lifting is avoided. Features Easy-to-clean surfaces ensure optimum hygiene. Undermount sink and tap. Integrated safety system prevents entrapment. 230 Actuator (motor) Control box Wired remote control Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Warranty Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Product	
ergonomically correct height. The table descends to a very low position, which offers the advantage that toddlers can easily climb up and down themselves. Thereby unnecessary lifting is avoided. Easy-to-clean surfaces ensure optimum hygiene. Undermount sink and tap. Integrated safety system prevents entrapment. 230 Actuator (motor) Control box Wired remote control Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Warranty Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Item number	R8685000
Undermount sink and tap. Integrated safety system prevents entrapment. 230 Actuator (motor) Control box Wired remote control Power consumption (maximum load) Poressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Ergonomy	The table descends to a very low position, which offers the advantage that toddlers
(V) Actuator (motor) Control box CBD6 (Linak), IP20 Wired remote control Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Features	Undermount sink and tap.
Control box Wired remote control Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Warranty Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the		230
Wired remote control Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Actuator (motor)	LA31 Deskline (Linak), 3500N, IPX1
Power consumption (maximum load) Power consumption by maximum load: 96 W Power consumption by standby: 0,1 W Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Control box	CBD6 (Linak), IP20
(maximum load) Power consumption by standby: 0,1 W Pressalit makes a commitment to remedy material and manufacturing defects for a period of three years from the invoicing date. Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the		HB30 (Linak), IPX4
Cleaning This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the		
This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged. The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Warranty	
long as they are diluted according to the instructions on the container. DISINFECTANTS: CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the	Cleaning	Do not use chlorine based, corrosive or abrasive cleaners as it may result in the
CaviCide The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the		
after cleaning, as some materials may otherwise be discolored and stained, and the		



PRESSALIT®

Product	
Item number	

Changing table, 31.5" x 70.9", electrically height adjustable, with sanitary appliances

R8685000

Mounting in different wall types

9	71	
	Concrete >B25 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.	
	Solid Brick >= Mz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.	
	Solid Sand Lime Brick >= Hlz12 V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. To be ordered separately.	
	Aerated Concrete P4 V8658 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs GB14. To be ordered separately.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood V8608 - Mounting kit, 6 lag bolts Ø10 x 70 - plugs SX12. NB! Plugs are not needed. To be ordered separately.	



PRESSALIT®

Product	Changing table, 31.5" x 70.9", electrically height adjustable, with sanitary appliances		
Item number	R8685000		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with 22 mm plywood Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.		
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (6 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.		
	Drywall (2 x 12,5 mm) water-resistant		
	Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.		

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com