
PRESSALIT®

| | |
|---|---|
| **Product** | PLUS fold down grab bar, vertical and horizontal adjustable |
| **Item number** | R3565112000 |
| | VVS:615852000<br>EAN:5708590357836 |
| **Color** | White |
| **Product description** | PLUS fold down grab bar, 30.3", ergonomically shaped to provide a clear sense of where the fold down grab bar ends. Left hand operated. Height adjustable by 9.5" and adjustable horizontally. Detachable and foldable. Anthracite cover plate for vertical wall track.<br>Materials: the grab bars are constructed of 3/8" anodized aluminium, with a non-slip gripping surface made of soft SEBS incorporating a glass-reinforced nylon core<br>For mounting on horizontal wall track (not included).<br><br>PLUS fold down grab bar, 30.3", ergonomically shaped to provide a clear sense of where the fold down grab bar ends. Left hand operated. Height adjustable by 9.5" and adjustable horizontally. Detachable and foldable. Anthracite cover plate for vertical wall track.<br>Materials: The arms are construced of 3/8" anodized aluminium, with a non-slip gripping surface made of soft SEBS incorporating a glass-reinforced nylon core<br>For mounting on horizontal wall track (not included). |
| **Adjustability** | Vertical and horizontal adjustable |
| **Adjustment height** | 9,46 inch |
| **Product capacity** | Maximum load: 330 lbs.<br>When the fold down grab bar is loaded with 330 lbs, each wall fastener in the horizontal wall track is loaded with 97 lbs.<br><br>*PLUS fold down grab bars have been tested statically with 1540 lbs (close to the wall), 935 lbs (in the middle) and 495 lbs (the outermost point).* |



PRESSALIT®

| | |
|---|---|
| **Product** | PLUS fold down grab bar, vertical and horizontal adjustable |
| **Item number** | R3565112000 |
| **Materials** | The grab bars are primarily constructed in 3/8" anodized aluminium, with a non-slip gripping surface at the end made of soft SEBS and incorporating a glass-reinforced nylon core.<br>The hinge arm is also made of soft SEBS.<br>Internal components and fasteners are primarily made of stainless steel.<br>The hinge barrel is capped with ABS polymer. |
| **Ergonomy** | The oval shape gives an easy and comfortable surface to lean and push against.<br>The end of the support arm is enlarged so that it is easier to pull forward from a sitting position and also provides a clear sense of where the support arm ends.<br>Soft and slip-resistant material that has a warm feel. |
| **Features** | Folds against the wall.<br>The underside is shaped for the mounting of various accessories. |
| **Warranty** | Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date. |
| **Cleaning** | This product should be cleaned with hot water or a mild cleaning solution.<br>Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.<br><br>The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.<br><br>DISINFECTANTS:<br>CaviCide<br><br>The product must be wiped down with a soft rag wrung out in clear water immediately after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.<br><br>DECALCIFICATION OF ALUMINUM PARTS:<br>Pressalit recommends that water deposits (Calcium, lime etc.) be removed from wall tracks and other aluminum parts using a solution of three parts of 30% acetic acid to seven parts tap water. When the aluminum parts have been washed down with this solution, the parts should be wiped over with a damp cloth wrung out in plain water. |

| | |
|---|---|
| **Product** | PLUS fold down grab bar, vertical and horizontal adjustable |
| **Item number** | R3565112000 |

**Intended use**
The fold down grab bar is used as a support for sitting down or getting up from a toilet, or for sideways transfer from a wheelchair.
**Operating environment**
For indoor use in a wet environment, such as a bathroom or a washroom, in private homes, nursing homes and hospitals.
For institutional use, the expected life time is 10 years.
*Life cycle test performed according to ISO 17966:2016.*

For maintenance, please refer to operation and maintenance manual, which is enclosed with the product, and which can also be found on the website under "Downloads".



Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com