

Product	PLUS shower seat 310, fixed height	
Item number	R7304112	
	VVS:777513012	
	NRF:6317087	
	EAN:5708590359328	
	HMI: 121181	
	FDA: INN/D135865	
Color	Anthracite gray	
Product description	PLUS shower seats are offered in a number of colours. They are available as both fixed height, electrically adjustable and manually adjustable, and with an option of back and armrests. They are suitable for wall-mounting or for fitting to Pressalit PLUS wall tracks.	
	PLUS shower seat 310. For fixed mounting. The seat is foldable. Materials: Comfortable polyurethane foam over a plywood core, fitted to an aluminit profile. Excl. mounting kit. <i>Replaces R7310</i>	
Adjustability	Fixed mounting	
Product capacity	Maximum user mass: 440 lbs. When the seat is loaded with 440 lbs, each wall fastener is loaded with 187 lbs.	
	The seat has been tested statically with safety factor 1.5, which is a requirement according to the applied assistive products standards.	
Materials	The shower seat is made of polyurethane (PU) foam with a plywood core and this i covered with a moulded coated surface that is protected using a clear PU lacquer. Internal components and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.	
Ergonomy	Ergonomically designed seat - contact surface are 12.2" x 14.4". Soft and slip- resistant material that has a warm feel.	
Features	The seat can fold up when not in use or to maximize floor space.	
Warranty	Pressalit makes a commitment to remedy material and manufacturing defects for a period of five years from the invoicing date.	



Product	PLUS shower seat 310, fixed height		
Item number	R7304112		
Cleaning			
	This product should be cleaned with hot water or a mild cleaning solution. Do not use chlorine based, corrosive or abrasive cleaners as it may result in the surface being damaged.		
	The following cleaning agents have been tested by Pressalit and may be used, as long as they are diluted according to the instructions on the container.		
	DISINFECTANTS:		
	Erisan OXY+		
	Tvättsprit 70% CaviCide surface disinfectant decontaminant cleaner		
	Rodalon Desinfektionsspray		
	Terralin protect (SCHÜLKE+)		
	Dismonzon Plus (BODE Chemie GmbH)		
	NON-DISINFECTANTS:		
	Wetrok Caledor (Wetrok)		
	Petrosol Citro (Büfa)		
	Important: Polyurethane surfaces of PLUS shower seats and PLUS backrests contains an antibacterial surface, which will be compromised if cleaned with anyth other than soap and water.		
	The product must be wiped down with a soft rag wrung out in clear water immedia after cleaning, as some materials may otherwise be discolored and stained, and the surface coating may deteriorate.		
	DECALCIFICATION OF ALUMINUM PARTS: Pressalit recommends that water deposits (Calcium, lime etc.) be removed from w tracks and other aluminum parts using a solution of three parts of 30% acetic acid		
	seven parts tap water. When the aluminum parts have been washed down with th solution, the parts should be wiped over with a damp cloth wrung out in plain water		
Declaration of conformity	This product is in compliance with all relevant requirements of regulation (EU) 2017/745 on medical devices.		



PLUS shower seat 310, fixed height Product R7304112 Item number Mounting in different wall types Concrete >B25 V8604 - Mounting kit, 4 countersunk bolts Ø8 x 70, plugs 0 .ß SX10. To be ordered separately. 0 Solid Brick >= Mz12 V8604 - Mounting kit, 4 countersunk bolts Ø8 x 70, plugs 0 SX10. To be ordered separately. 0 Solid Sand Lime Brick >= HIz12 V8604 - Mounting kit, 4 countersunk bolts Ø8 x 70, plugs 0 SX10. To be ordered separately. 0 0 **Aerated Concrete P4** V8654 - Mounting kit, 4 countersunk bolts M8 x 35, plugs 0 FTP M 8. To be ordered separately. 0 Drywall (2 x 12,5 mm) water-resistant, re-enforced with wood 0 V8604 - Mounting kit, 4 countersunk bolts Ø8 x 70, plugs SX10. NB! Plugs are not needed. To be ordered separately.



Product Item number	PLUS shower seat 310, fixed height R7304112	
	<b>Drywall (2 x 12,5 mm) water-resistant, re-enforced with</b> <b>22 mm plywood</b> Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	Drywall (2 x 12,5 mm) water-resistant, re-enforced with steel plates (.08 inch) Wall fasteners (4 pcs) must be bought separately, for drywall it is possible to use e.g. SnapTight or WingIt anchors or similar.	
	<b>Drywall (2 x 12,5 mm) water-resistant</b> Mounting in this wall type is not recommended - risk of fatal injury to persons and walls.	<u>!</u>

It is the responsibility of the installer to ensure that suitable wall fasteners are used.

#### pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

