

## PRESSALIT.

Product	PLUS replacement shower seat 450 with aperture, manually height adjustable
Item number	R7115112
	VVS:777514212
	NRF:6317067
	EAN:5708590359014
	FDA: INN/D135865
Color	Anthracite gray
Product description	PLUS shower seats are offered in a number of colours. They are available as both fixed height, electrically adjustable and manually adjustable, with and without aperture, and with an option of back and armrests.  They are suitable for wall-mounting or for fitting to Pressalit PLUS wall tracks.
	PLUS shower seat 450 with aperture. Manually height adjustable by 9.4", without the use of tools. The seat is foldable.  Materials: Comfortable polyurethane foam over a plywood core, fitted to an aluminium profile.  For mounting on vertical wall track (not included).  Replaces R7401
Adjustability	Height adjustable
Adjustment height	9,46 inch
Product capacity	Maximum user mass: 440 lbs. When the seat is loaded with 440 lbs, each wall fastener is loaded with 77 lbs.
	The seat has been tested statically with safety factor 1.5, which is a requirement according to the applied assistive products standards.
Materials	The shower seat is made of polyurethane (PU) foam with a plywood core and this is covered with a moulded coated surface that is protected using a clear PU lacquer. Internal components and fasteners are primarily made of stainless steel. The hinge barrel is capped with ABS.
Ergonomy	Ergonomically designed seat - contact surface are 12.2" x 14.4". Soft and slip-resistant material that has a warm feel.
Features	The seat can fold up when not in use or to maximise floor space.



## PRESSALIT.

JS replacement shower seat 450 with aperture, manually height ustable
R7115112
salit makes a commitment to remedy material and manufacturing defects for a od of five years from the invoicing date.
product should be cleaned with hot water or a mild cleaning solution.  not use chlorine based, corrosive or abrasive cleaners as it may result in the ace being damaged.
following cleaning agents have been tested by Pressalit and may be used, as as they are diluted according to the instructions on the container.
NFECTANTS: an OXY+ tsprit 70% Cide surface disinfectant decontaminant cleaner alon Desinfektionsspray alin protect (SCHÜLKE+) nonzon Plus (BODE Chemie GmbH)
I-DISINFECTANTS: rok Caledor (Wetrok) osol Citro (Büfa)
ortant: Polyurethane surfaces of PLUS shower seats and PLUS backrests ains an antibacterial surface, which will be compromised if cleaned with anything r than soap and water.
product must be wiped down with a soft rag wrung out in clear water immediately cleaning, as some materials may otherwise be discolored and stained, and the ace coating may deteriorate.
ALCIFICATION OF ALUMINUM PARTS: salit recommends that water deposits (Calcium, lime etc.) be removed from wall as and other aluminum parts using a solution of three parts of 30% acetic acid to en parts tap water. When the aluminum parts have been washed down with this tion, the parts should be wiped over with a damp cloth wrung out in plain water.
product is in compliance with all relevant requirements of regulation (EU) 7/745 on medical devices.



## PRESSALIT®

Product	PLUS replacement shower seat 450 with aperture, manually height adjustable
Item number	R7115112

pressalit.com

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com