





PRESSALIT®

Pressalit 1000 304 Standard toilet seat incl. fixed hinge in stainless steel

Item number	304000-BG4999 EAN:5708590189697 Pressalit 1000 is a universal toilet seat in excellent quality and particularly suited to building projects.	
Color	White	
Description	<p>PRESSALIT toilet seat with cover, model "1000", art. no. 304 made of colour ingrained duroplast with BG4 fixed hinge of stainless steel</p> <ul style="list-style-type: none">- centre distance: 155 mm- load - ring seat 240 kg- suitable for many universal toilets- 10 year guarantee	
		
Design type	Sandwich	
Designer	Pressalit	
Design year	2001	
Materials	<p>TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.</p> <p>BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).</p> <p>DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.</p> <p>MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.</p>	
Product capacity	Load - ring seat 240 kg	



PRESSALIT®

Pressalit 1000 304
Standard toilet seat incl. fixed hinge in stainless steel

Weight	2,2416 kg
Carton size	455x390x70 mm
Gross weight	2,6416 kg
Crate size	478x400x357 mm
Weight per crate	13,208 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	<p>Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.</p> <p>In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.</p> <p>Subject to changes in the product range, technical changes and printing errors.</p>

pressalit.com
