

# PRESSALIT.

### Pressalit Scandinavia 75 Standard toilet seat incl. hinge in stainless steel

Item number	75000-D43999 EAN:5708590292908 Pressalit Scandinavia first appeared in 1975 and is still a unique classic that fits most toilet pans.
Colour	White
Description	<ul> <li>PRESSALIT toilet seat with cover, model</li> <li>"Scandinavia", art. no. 75 made of colour ingrained duroplast with D43 top mounted hinge of stainless steel.</li> <li>centre distance: 85 - 185 mm</li> <li>load - ring seat 240 kg</li> <li>suitable for many universal toilets</li> <li>10 year guarantee</li> </ul>
	410 410 -450 -450 -375 -450 -4
Design type	Sandwich
Designer	Sigvard Bernadotte, Acton Bjørn
Design year	1975
Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.
	BUFFERS: EVA (copolymer made of ethylene and vinyl acetate).
	DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts.
	MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.



## PRESSALIT.

### Pressalit Scandinavia 75 Standard toilet seat incl. hinge in stainless steel

Product capacity	Load - ring seat 240 kg
Weight	2,95 kg
Carton size	457x389x68 mm
Gross weight	3,25 kg
Crate size	469x401x348 mm
Weight per crate	16,25 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.
Warranty	Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint. br> br> ln the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.
	Subject to changes in the product range, technical changes and printing errors.
	Subject to changes in the product range, technical changes and printing errors.

### pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com

