


Pressalit Objecta / Projecta / Projecta Plus 54
Standard toilet seat with Polygiene® incl. Anti-vandal hinge in stainless steel

Item number	54011-BZ1999 EAN:5708590321622
	Pressalit Objecta/Projecta/Projecta Plus. The toilet seats are suitable for most standard toilets and contain a Polygiene effect, which prevents the growth of bacteria 24/7. Particularly suited to building projects.
Colour	White
Description	PRESSALIT toilet seat with cover, model "Projecta Plus", art.no. 54 made of colour ingrained duroplast with polygiene incl. BZ1 antivandal hinge in stainless steel. - centre distance: 95 - 195 mm - load - ring seat 240 kg - 10 year guarantee









Design type	Sandwich
Designer	Pressalit
Design year	1982

Pressalit Objecta / Projecta / Projecta Plus 54
Standard toilet seat with Polygiene® incl. Anti-vandal hinge in stainless steel

Materials	TOILET SEAT: The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing. POLYGIENE (only relevant for toilet seats with polygiene): Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day. BUFFERS: EVA (copolymer made of ethylene and vinyl acetate). DAMPER KIT (only relevant for toilet seats with soft close): Hydraulic damper with stainless steel damper casing and thermoplastic parts. MOUNT/HINGES: Stainless steel model W. no. 1.4301/M and thermoplastic.
Product capacity	Load - ring seat 240 kg
Weight	2,457 kg
Carton size	457x389x68 mm
Gross weight	2,857 kg
Crate size	469x401x348 mm
Weight per crate	14,285 kg
Qty per crate	5
Crates per pallet	18
Qty per pallet	90
Cleaning	Use a mild soap solution to clean the seat. Please take care that the seat and hinges are not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has been flushed away.

Pressalit Objecta / Projecta / Projecta Plus 54
Standard toilet seat with Polygiene® incl. Anti-vandal hinge in stainless steel

Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.

In the event of complaints about defective materials and/or manufacturing defects and/or functional limitations ascertained within a 10-year period, following proper use and cleaning of the toilet seat (we reserve the right to examine the toilet seat at our factory), Pressalit will deliver spare parts or replace the toilet seat by an identical or similar model. If the color is no longer available, Pressalit reserves its right to replace the toilet seat by a similar model in the color white. Upon replacement or delivery of a spare part, the warranty period will not be extended nor renewed. If replacement is not possible, Pressalit may instead refund the purchase price.

Subject to changes in the product range, technical changes and printing errors.

Pressalit A/S
Pressalitvej 1
DK-8680 Ry
Tel.: +45 8788 8788
Fax: +45 8788 8789
E-mail: pressalit@pressalit.com