

## PRESSALIT®

Pressalit Projecta D without cover 879 Standard toilet seat with Polygiene®, without cover, incl. universal institutional hinge in stainless steel

879011-DC7999 Item number

EAN:5708590326658

Pressalit Projecta D - without cover. The toilet seat fits most D-shaped toilets and contains a Polygiene effect, which prevents the growth of bacteria 24/7. That's why these toilet seats are particularly suited to building

projects.

Colour White


**Description** PRESSALIT toilet seat without cover, model "Projecta D" art. no. 879 made of colour ingrained duroplast with


DC7 special hinge in stainless steel.

- centre distance: 158 mm

- ring seat 240 kg

- 10 year guarantee







Designer Pressalit 2002 Design year



## PRESSALIT.

Pressalit Projecta D without cover 879 Standard toilet seat with Polygiene®, without cover, incl. universal institutional hinge in stainless steel

Materials TOILET SEAT:

The material is colour ingrained duroplast (UF A 10 = urea formaldehyde) that contains no environmentally hazardous substances. UF plastic comprises 67% urea formaldehyde resin, 28% cellulose, as well as 5% minerals, pigments, lubricants and moisture content. The raw material from the supplier contains up to 0.03% free formaldehyde and even less following curing.

POLYGIENE (only relevant for toilet seats with polygiene):

Polygiene consists of biocide silver chloride, which has an anti-bacterial effect. This is why the bacteria growth is hampered 24 hours a day.

**BUFFERS:** 

EVA (copolymer made of ethylene and vinyl acetate).

DAMPER KIT (only relevant for toilet seats with soft close):

Hydraulic damper with stainless steel damper casing and thermoplastic parts.

MOUNT/HINGES:

Stainless steel model W. no. 1.4301/M and thermoplastic.

Product capacity Load - ring seat 240 kg

Weight 1,756 kg

Carton size 457x389x68 mm

Gross weight 2,146 kg

**Crate size** 469x401x348 mm

Weight per crate 10,73 kg

Qty per crate 5

Crates per pallet 18

Qty per pallet 90

Cleaning Use a mild soap solution to clean the seat. Please take care that the seat and hinges are

not left damp. Dry off any residual water or cleaning agent with a soft cloth. Avoid contact of the seat and hinges with abrasive, corrosive or chlorine-based cleaners, as these may cause damage or lead to flash rust. Therefore, when cleaning the bowl, make sure that the seat and cover are kept in an upright position until all cleaning agent has

been flushed away.



## PRESSALIT.

Pressalit Projecta D without cover 879 Standard toilet seat with Polygiene®, without cover, incl. universal institutional hinge in stainless steel

## Warranty

Your Pressalit toilet seat is subject to a 10-year product warranty against presentation of receipt. You should contact the dealer or store where you purchased the seat in the event of a complaint.<br/>

| Strict | Stri

Subject to changes in the product range, technical changes and printing errors.

pressalit.com

Pressalit A/S Pressalitvej 1 DK-8680 Ry Tel.: +45 8788 8788 Fax: +45 8788 8789 E-mail: pressalit@pressalit.com